www.equip-info.net

USB 2.0 Card Reader int. 3.5" + USB port

Universal | 128577 | Page 1/2

Features

- Easily mount into 3.5" drive bay, powered by USB port (DC + 5V)
- Includes beige, black and silver color bezel for swapping.
- Supported SM/xD, SD/MMC, MS and CF/MD memory slots.
- Allows direct data transfer between different types of memory cards.
- Mini size, suitable for all desktop PC enclosure.
- USB 2.0 high-speed data transfer rate up to 480Mbps.
- Fully backward compatible with USB 1.1 devices.
- Two LED indicators for in-use status.
- All media slots can be used at the same for data exchange.
- 1x USB 2.0 downstream port for convenient access.

Package Contents

1 x 3.5" Int. Card Reader

1 x User Manual (G/E)

3 x Color Bezels

Set of screws

Memory Cards Supported

- SD, MMC I/II, MMC 4.0, MMC Dual Voltage, RS MMC, RS MMC Dual Voltage, RS MMC 4.0, xD, xD (M), xD (H)
- MS, MS Pro, MS Magic Gate, MS-Pro Magic Gate, HS-MS-Pro Magic Gate, MS-Duo, MS Pro-Duo, MS Pro-Duo PSP, MS Pro-Duo Gaming, HS-MS-Pro Duo, MS-Duo Magic Gate, MS Pro-Duo Magic Gate, CF I/II, CF Ultra II, CF Extreme III

Maximum Capacity of Memory Card Supported

SD :	16GB
SDHC:	32GB
MMC:	16GB
MS:	16GB
CF:	32GB
xD:	2GB

www.equip-info.net

USB 2.0 Card Reader int. 3.5" + USB port

Universal | 128577 |

Specifications

LED Indicator	Power-on LED Memory card in-use LED
Bus Interface	USB 2.0 or 1.1
Power Supply	5V by USB Port
Operating Temperature	0 ~ 50°C
Storage Temperature	-10 ~ 60°C
Cable	USB 2.0 Cable, 60cm length
Dimensions	96.2(L)*102.1(W)*25.4(H) mm
Weight	230g
Certification	FCC Class B, CE
OS Supported	Windows 98/SE/ME Windows 2000, 2003 Server Windows XP/Vista 32/64-bit Mac OS9.2 or Higher Linux OS 2.4.X or Higher